



ARCHON

MOVING LIFE FORWARD



HOWO
PROFESSION DRIVES DREAM. SERVICE LOADS TRUST

LIUGONG
TOUGH WORLD. TOUGH EQUIPMENT.

HEAVY AND LIGHT TRUCKS

Homan C3B CUBIC DUMPRUCK 4X2 / 4X4



DRIVING TYPE: 4X2, 4X4 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4E160-3 (YUCHAI, EURO 2, 4.257L, 160HP) / WP4.10150E5 (WEICHAI, EURO 5, 4.088L, 150HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3 TONS
REAR AXLE: 9 TONS
WHEEL BASE: 3400 MM
TIRES: 9.00 R20
FUEL TANK: 120 LITERS
LOAD CAP: 6.5 M3
BOX DIMENSION: 3850MM X 2100MM X 800MM

Homan C5B CUBIC DUMPRUCK 4X2 / 4X4



DRIVING TYPE: 4X2, 4X4 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC6J220-33 (YUCHAI, EURO 2, 6.494L, 220HP) / WP4.6N0220E50 (WEICHAI, EURO 5, 4.580L, 220HP)
GEAR BOX: HW90510C / 10 FORWARD & 2 REVERSE
FRONT AXLE: HF7 7 TONS
REAR AXLE: MCX1626 16 TONS
WHEEL BASE: 3600 MM
TIRES: 10.00 R20
FUEL TANK: 300 LITERS
LOAD CAP: 18-20 TONS
BOX LENGTH: 4500MM

Homan C3B BOOM CRANE 3.2 TONS 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4D130-33 (YUCHAI, EURO 2, 4.214L, 130HP) / WP2.3N0130E50 (WEICHAI, EURO 5, 2.29L, 130HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 2.4 TONS
REAR AXLE: 4.2 TONS
WHEEL BASE: 3800 MM
TIRES: 7.50 R16
FUEL TANK: 120 LITERS
LIFTING CAP: 3.2 TONS

Homan C5B BOOM CRANE 5 TONS 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC6J190-33 (YUCHAI, EURO 2, 6.494L, 190HP) / WP4.6N0220E50 (WEICHAI, EURO 5, 4.580L, 220HP)
GEAR BOX: HW90510C / 10 FORWARD & 2 REVERSE
FRONT AXLE: 3.6 TONS
REAR AXLE: 10 TONS
WHEEL BASE: 5200 MM
TIRES: 10.00 R20
FUEL TANK: 300 LITERS
LIFTING CAP: 5 TONS

Homan C3B TRANSIT MIXER 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4D140-33, YC4D140-33 (YUCHAI, EURO 2, 4.214L, 130/140 HP) / WP4.10150E50 (WEICHAI, EURO 5, 4.088L, 190HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3 TONS
REAR AXLE: 9 TONS
WHEEL BASE: 3900 MM
TIRES: 9.00 R20
FUEL TANK: 120 LITERS
LOAD CAP: 4M3 / 6M3

Homan C5B TRANSIT MIXER 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC6A220-33 (YUCHAI, EURO 2, 7.255L, 260 HP) / WP4.6N0220E50 (WEICHAI, EURO 5, 4.494L, 220HP)
GEAR BOX: HW90510C / 10 FORWARD & 2 REVERSE
FRONT AXLE: 3 TONS
REAR AXLE: 9 TONS
WHEEL BASE: 4200 MM
TIRES: 10.00 R20
FUEL TANK: 300 LITERS
LOAD CAP: 6M3 / 7M3

Homan C3B GARBAGE COMPACTOR 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4E140-33 (YUCHAI, EURO 2, 4.257L, 140HP) / WP4.10150E50 (WEICHAI, EURO 5, 4.088L, 150HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3 TONS
REAR AXLE: 9 TONS
WHEEL BASE: 3400 MM
TIRES: 9.00 R20
FUEL TANK: 120 LITERS
MAX CAPACITY: 5M3

Homan C5B GARBAGE COMPACTOR 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC6J190-33 (YUCHAI, EURO 2, 6.494L, 190HP) / WP4.6N0220E50 (WEICHAI, EURO 5, 4.580L, 220HP)
GEAR BOX: HW90510C / 10 FORWARD & 2 REVERSE
FRONT AXLE: 3.6 TONS
REAR AXLE: 10 TONS
WHEEL BASE: 4200 MM
TIRES: 9.00 R20
FUEL TANK: 300 LITERS
MAX CAPACITY: 8M3, 10M3, 12M3

Homan C5B DROPSIDE CARGO TRUCK 4X2 18 TONS



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC6J190-33 (YUCHAI, EURO 2, 6.494L, 190HP) / WP4.6N0220E50 (WEICHAI, EURO 5, 4.580L, 220HP)
GEAR BOX: HW90510C / 10 FORWARD & 2 REVERSE
FRONT AXLE: HF7 7 TONS
REAR AXLE: MCX1626 16 TONS
WHEEL BASE: 5600 MM
TIRES: 9.00 R20
FUEL TANK: 300 LITERS
LOAD CAP: 18 TONS

Homan C3B WATER TANKER 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4FA115-33 (YUCHAI, EURO 2, 2.98L, 115HP) / WP2.3Q110E50 (WEICHAI, EURO 5, 2.29L, 110HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3 TONS
REAR AXLE: 9 TONS
WHEEL BASE: 3300 MM
TIRES: 9.00 R20
FUEL TANK: 120 LITERS
MAX VOLUME: 4M3

Homan C3B DROPSIDE CARGO 4X2 10-12 TONS



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 CABIN WITHOUT SLEEPER
ENGINE: YC4E160-33 (YUCHAI, EURO 2, 4.257L, 160HP) / WP4.10150E50 (WEICHAI, EURO 5, 4.088L, 165HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3.2 TONS
REAR AXLE: 8 TONS
WHEEL BASE: 4200 MM
TIRES: 8.25 R20
FUEL TANK: 150 LITERS
LOAD CAP: 10-12 TONS
BOX SIZE: 5200MM X 2100MM X 550MM

Homan C3B DROPSIDE CARGO 4X2 13-15 TONS



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4E160-33 (YUCHAI, EURO 2, 4.257L, 160HP) / WP4.10150E50 (WEICHAI, EURO 5, 4.088L, 165HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 3.6 TONS
REAR AXLE: 10 TONS
WHEEL BASE: 5200 MM
TIRES: 9.00 R20
FUEL TANK: 200 LITERS
LOAD CAP: 13-15 TONS
BOX SIZE: 6800MM X 2300MM X 600MM

Homan C3B DROPSIDE CARGO 4X2 8-10 TONS



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 CABIN WITHOUT SLEEPER
ENGINE: YC4D130-33 (YUCHAI, EURO 2, 4.214L, 130HP) / WP3.N0160E50 (WEICHAI, EURO 5, 2.97L, 160HP)
GEAR BOX: WLY6TSSC / 10 FORWARD & 2 REVERSE
FRONT AXLE: 2.7 TONS
REAR AXLE: 7.2 TONS
WHEEL BASE: 3800 MM
TIRES: 8.25 R20 / 8.25 R20
FUEL TANK: 120/200 LITERS
LOAD CAP: 8-10 TONS
BOX SIZE: 6100MM X 2100MM X 550MM

Homan C3B MAN LIFTING 4X2



DRIVING TYPE: 4X2 LEFT HAND
CAB: 2080 EXTENDED CABIN
ENGINE: YC4D130-33 (YUCHAI, EURO 2, 4.214L, 130HP) / WP2.3N0130E50 (WEICHAI, EURO 5, 2.29L, 130HP)
GEAR BOX: 8JS85F / 8 FORWARD & 2 REVERSE
FRONT AXLE: 2.7 TONS
REAR AXLE: 7.2 TONS
WHEEL BASE: 3900 MM
TIRES: 7.50 R16
FUEL TANK: 120 LITERS
MAX BOOM LENGTH: 14 METERS

HOWO 7 SELF LOADING



DRIVING TYPE: 6X4, LEFT HAND
CAB: HOWO 7 LENGTHENED CAB
ENGINE: WEICHAI 380, 400 HP EURO 2 INTERCOOLER TURBO CHARGER
TRANSMISSION: HW19710 (10 FORWARD & 2 REVERSE)
REAR AXLE: MCX1626 (16 TONS)
FRONT AXLE: VG695 (9.5 TONS)
STEERING: BOSCH
TIRES: 315/ 80 R X 22.5
FUEL TANK: 400 LITERS
LOAD CAP: 25 TONS
CARGO BED: 25 FT

HOWO T7 CAB AND CHASSIS



DRIVING TYPE: 8X4, LEFT HAND
CAB: 17H LENGTHENED CAB
ENGINE: WEICHAI 380, 400 HP EURO 2 INTERCOOLER TURBO CHARGER
TRANSMISSION: HW19710 (10 FORWARD & 2 REVERSE)
REAR AXLE: MCX1626 (16 TONS)
FRONT AXLE: VG695 (9.5 TONS)
STEERING: BOSCH
TIRES: 315/ 80 R X 22.5
FUEL TANK: 400 LITERS
LOAD CAP: 32 TONS

TRAILERS

TRI-AXLE LOWBED TRAILER



DIMENSIONS:
LENGTH OF LOADING PLATFORM (MM): 5000
HEIGHT OF LOADING PLATFORM (MM): 500
KING PIN SETTING:
FIFTH WHEEL HEIGHT (MM):

KING PIN SIZE:

LENGTH X WIDTH: 14,500 X 3,050
APPROXIMATE 5,600 KG
APPROXIMATE 650 MM
500 MM
THE HEIGHT WILL BE ADJUSTED ACCORDING TO THE TRACTOR SPECIFICATION
50MM / 90MM (OPTIONAL)

AXLE SPACE (MM): 10,155 + 1,310 + 1,310
TARE WEIGHT (KG): APPROXIMATE 12,000
PAYLOAD (KG): 60,000
GVWR (KG): 82,000
TIRES: 8,25 X 22.5
AXLE: 3X (FUWA AXLE)

TRI-AXLE FLATBED TRAILER



DIMENSIONS:
LENGTH OF LOADING PLATFORM (MM):
KING PIN SETTING:
FIFTH WHEEL HEIGHT (MM):

PAYLOAD (KG): 60,000
TIRES: 11R22.5
AXLE: 3 X 13T (FUWA AXLE)
KING PIN SIZE: 58MM

LENGTH X WIDTH: 12,399 X 2,480
APPROXIMATE 1,460 MM
1,050 MM
THE HEIGHT WILL BE ADJUSTED ACCORDING TO THE TRACTOR SPECIFICATION
60,000
11R22.5
3 X 13T (FUWA AXLE)
58MM

CLG6611E

ROAD ROLLER



ENGINE: CUMMINS BTA43.9 KW / 125 HP @ 2200 RPM
EURO 4 (HYDRAULIC DRIVE MODE)
PEAK TORQUE: 480 NM,
TURBOCHARGED, 4 CYLINDERS
23.1 X 26 12 PLY RATING

TIRE SIZE: 11.350 TONS (VIBRATING DRUMS)
6.350 TONS, DRIVE AXLE 5 TONS

HYDRAULIC DRIVE MODE: PUMP 1 FOR JOYSTICK SHIFTING
(REVERSE AND FORWARD)
PUMP FOR VIBRATION

WHEEL BASE: 2,980MM
OPERATORS CAB: OPEN CAB

NUMBER OF AMPLITUDE SETTINGS: 2 (1 LOW AMPLITUDE AND 1 HIGH AMPLITUDE)
GRADEABILITY: 45% (25 DEGREES)

CLG922E

CRAWLER EXCAVATOR



ENGINE: CUMMINS QSB7 TIER 3 (6 CYLINDER INLINE
TURBOCHARGED) 124 KW (166HP @ 2050 RPM)
TORQUE 614NM @1500 RPM DISPLACEMENT 6.7 L

BUCKET CAPACITY: 1.0 CUBIC METER
HYDRAULIC SYSTEM: KAWASAKI PUMP
(MAX PRESSURE 5,410 PSI (37.3MPA))

TRACK SHOE WIDTH & SECTION PER SIDE: 23.6 INCHES (600MM) 49 PCS.
TRACK LENGTH: 4,440 MM (14.6 FT)
CHASSIS WIDTH: 2,390 MM

BOTTOM ROLLERS EACH SIDE: 8

ARM LENGTH: 2,915 MM
BOOM LENGTH: 5,710 MM
OPERATING WEIGHT: 22,000 KG
OPERATORS CAB: AIR CONDITIONED
GRADEABILITY: 35 DEGREES
BREAKOUT FORCE (GROUND PRESSURE): 105 KPA

CLG855H

WHEEL LOADER



ENGINE: CUMMINS 6LT 9.3 STAGE 2 / TIER 2
6 CYLINDER 162 KW (217HP @2000 RPM)
TORQUE 980 NM @2000 RPM DISPLACEMENT
9.3 L, TURBO CHARGED
3 CUBIC METER

BUCKET CAPACITY: 165 KN
BREAKOUT FORCE: LIUGONG BRAND 1 REVERSE AND 2 FORWARD
(AT SELECTOR SPOOL)
TRANSMISSION: GEAR TYPE MAIN RELIEF PRESSURE (18MPA)

HYDRAULIC SYSTEM: DUMP CLEARANCE AT FULL HEIGHT DISCHARGE: 3,056 MM
WHEEL BASE: 3,250 MM
TIRE SIZE: 23.5 X 25
OPERATING WEIGHT: 16,700 KG
OPERATORS CAB: AIR CONDITIONED
HINGE JOINTS: TAPERED ROLLER BEARINGS

CLG6110E

ROAD ROLLER



ENGINE: SHANGCHAI SC4H140.2G2 103/138HP
@2000 RPM EURO 2 (MECHANICAL),
PEAK TORQUE 535NM
TURBO CHARGED 4 CYLINDERS
17.5 X 25 12 PLY RATING

TIRE SIZE: 10 TONS (VIBRATING DRUM 5 TONS,
DRIVE AXLE 5 TONS)

OPERATING WEIGHT: 10 TONS

TRANSMISSION: MT WITH TRANSFER CASE GEAR
(2 REVERSE AND 3 FORWARD)
2,900MM

WHEEL BASE: AIR CONDITIONED
OPERATORS CAB: AIR CONDITIONED

NUMBER OF AMPLITUDE SETTINGS: 2 (1 LOW AMPLITUDE AND 1 HIGH AMPLITUDE)
GRADEABILITY: 30% (17 DEGREES)

CLG920E

CRAWLER EXCAVATOR



ENGINE: CUMMINS QSB7 TIER 3 (6 CYLINDER INLINE
TURBOCHARGED) 124 KW (166HP @ 2050 RPM)
TORQUE 614NM @1500 RPM DISPLACEMENT 6.7 L

BUCKET CAPACITY: 1.0 CUBIC METER
HYDRAULIC SYSTEM: INLINE PUMP
(MAX PRESSURE 5,410 PSI (37.3MPA))

TRACK SHOE WIDTH & SECTION PER SIDE: 23.6 INCHES (600MM) 49 PCS.
TRACK LENGTH: 4,160 MM (13.6 FT)
CHASSIS WIDTH: 2,280 MM

BOTTOM ROLLERS EACH SIDE: 7

ARM LENGTH: 2,915 MM
BOOM LENGTH: 5,710 MM
OPERATING WEIGHT: 21,500 KG
OPERATORS CAB: AIR CONDITIONED
GRADEABILITY: 35 DEGREES
BREAKOUT FORCE (GROUND PRESSURE): 105 KPA

CLG835H

WHEEL LOADER



ENGINE: YUCHAI YC6J125Z-T22 STAGE 2 / TIER 2
6 CYLINDER 92 KW (123 HP) @ 2,000 RPM
TORQUE 608 NM @1,300 RPM
DISPLACEMENT 6.494 L TURBOCHARGED
1.8 CUBIC METER

BUCKET CAPACITY: 102 KN (10,200 KG)
BREAKOUT FORCE: LIUGONG BRAND 1 REVERSE AND 2 FORWARD
(AT SELECTOR SPOOL)
TRANSMISSION: GEAR TYPE MAIN RELIEF PRESSURE (22MPA)

HYDRAULIC SYSTEM: DUMP CLEARANCE AT FULL HEIGHT DISCHARGE: 2,938 MM
GROUND TO FULL REACH: 1,035 MM
WHEEL BASE: 2,870 MM
TIRE SIZE: 17.5 X 25
OPERATING WEIGHT: 10,125 KG
OPERATORS CAB: AIR CONDITIONED
HINGE JOINTS: TAPERED ROLLER BEARINGS



CLG4165D

MOTORGRADER



ENGINE: CUMMINS 6BTA 5.9-C160 STAGE 2 / TIER 2,
6 CYLINDER 132 KW (177 HP / 180 PS)
@2,200 RPM, TORQUE 787 NM @1,400RPM
DISPLACEMENT 5.9 L TURBOCHARGED
AIR TO AIR INTERCOOLED

TRANSMISSION: LIUGONG BRAND POWER SHFT 3 REVERSE
(26.5 KM/H) AND 6 FORWARD (42 KM/H)

HYDRAULIC SYSTEM: GEAR TYPE MAIN RELIEF PRESSURE (20MPA)

AXLES: FINAL DRIVE - CHAIN DRIVE
FRONT AXLE - WHEEL LEAN ANGLE
LEFT/RIGHT 18 DEGREES

WHEEL BASE: 6,230 MM
TIRE SIZE: 17.5 X 5
OPERATING WEIGHT: 15,000 KG
OPERATORS CAB: AIR CONDITIONED

MOLDBOARD (BLADE) STANDARD LENGTH: 3,660MM (3,66M)
MOLDBOARD (BLADE) CUTTING DEPTH: 600MM
MOLDBOARD (BLADE) STANDARD THICKNESS: 19MM

CLG4140D

MOTORGRADER



ENGINE: CUMMINS 6BTA 5.9-C160 STAGE 2 / TIER 2,
6 CYLINDER 118 KW (158 HP / 160 PS)
@2,200 RPM, TORQUE 670 NM @1,300RPM
DISPLACEMENT 5.9 L TURBOCHARGED
AIR TO AIR INTERCOOLED

TRANSMISSION: LIUGONG BRAND POWER SHFT 3 REVERSE
(26.5 KM/H) AND 6 FORWARD (42 KM/H)
GEAR TYPE MAIN RELIEF PRESSURE (20MPA)

HYDRAULIC SYSTEM: FINAL DRIVE - CHAIN DRIVE
FRONT AXLE - WHEEL LEAN ANGLE
LEFT/RIGHT 18 DEGREES

AXLES:

WHEEL BASE: 5,930 MM
TIRE SIZE: 13 X 24
OPERATING WEIGHT: 12,600 KG
OPERATORS CAB: AIR CONDITIONED

MOLDBOARD (BLADE) STANDARD LENGTH: 3,660MM (3,66M)
MOLDBOARD (BLADE) CUTTING DEPTH: 600MM
MOLDBOARD (BLADE) STANDARD THICKNESS: 19MM

CLG764B

BACKHOE LOADER



ENGINE: YUCHAI YC4A105Z-T20 2 / STAGE II
75 KW (102HP) @ 2,200 RPM 72 KW
(98HP) @ 2,200 RPM 400NM
@1,500 RPM 4.8 L

TRANSMISSION: 4 FORWARD (9.8 KM/H 17.5 KM/
H 28 KM/H 44 KM/H)

DRIVE TRAIN: 4 WHEEL DRIVE

HYDRAULIC SYSTEM: GEAR TYPE MAIN RELIEF PRESSURE
(21.5 MPA)

TIRES: FRONT (14-17.5 NHS-14PR-T) TIRE
(16/70-24)

OPERATING WEIGHT: 8,300 KG
BUCKET CAPACITY: 1.0 M3 (LOADER)

DUMP REACH AT FULL HEIGHT DISCHARGE: 713 MM (LOADER)
BUCKET CAPACITY: 0.2 M3 (BACKHOE)
LOADING HEIGHT: 3,586 MM (BACKHOE)
CABIN: AIR CONDITIONED

AFTERSALES SERVICES

- ✓ OVERHAULING
- ✓ REPLACE OR REPAIR
- ✓ ON-SITE RESCUE
- ✓ FABRICATION
- ✓ TRUCK REHAB
- ✓ PREVENTIVE MAINTENANCE SERVICES



SPAREPARTS



HEAD OFFICE SHOWROOM

SPECS COMPARISON

HOWO TX



HOWO T7S



HOWO V7X



HOWO 7



HOWO NX



	HOWO TX	HOWO T7S	HOWO V7X	HOWO 7	HOWO NX
GROUND CLEARANCE	685 mm (27 inches)	635 mm (25 inches)	635 mm (25 inches)	736 mm (29 inches)	635 mm (25 inches)
FUEL CONSUMPTION RATIO	1:4 when empty 1:2 when loaded	1:4 when empty 1:2 when loaded	1:4 when empty 1:2 when loaded	1:4 when empty 1:2 when loaded	1:4 when empty 1:2 when loaded
FUEL TANK CAPACITY	400 Liters	300 Liters	400 Liters	300 Liters	300 Liters
REAR AXLE MODEL	MCX16ZG (16 TONS)	MCX16ZG (16 TONS)	MCX16ZG (16 TONS)	MCX16ZG (16 TONS)	MCX16ZG (16 TONS)
FRONT AXLE MODEL	VGD95 (9.5 TONS)	VGD95 (9.5 TONS)	VGD95 (9.5 TONS)	VGD95 (9.5 TONS)	VGD95 (9.5 TONS)
CHASSIS THICKNESS	8mm X 8mm(Q345)	8mm X 8mm(Q345)	8mm X 8mm(Q345)	8mm X 8mm(Q345)	8mm X 8mm/8mm X 5mm(Q235)
BRAKE LINING SIZE (FRONT AND REAR)	410mm×160mm(front) 420mm×185mm(rear) wider	410mm×160mm(front) 420mm×185mm(rear)	410mm×160mm(front) 420mm×185mm(rear) wider	410mm×160mm(front) 420mm×185mm(rear)	410mm×160mm(front) 420mm×185mm(rear)
CABIN DESIGN	MAN TGS SERIES	VOLVO FH	FMX VOLVO	FL10 VOLVO	HOHAN

BRANCHES NATIONWIDE

Luzon

CALOOCAN

Lots 6 & 7, Barangay 8, Dagat-Dagatan Ave., Caloocan City, 1400
0917 104 7440 Sales | 0966 142 5782 Helpdesk
0917 628 4179 Aftersales

EDSA

1249 Edsa Balintawak Quezon City, 1106
0917 104 7440 Sales | 0966 142 5782 Helpdesk
0917 628 4179 Aftersales

Visayas

CEBU

Ouano Avenue, NRA Barangay Subangdaku Mandaue City, Cebu 6014
0936 372 3585 Sales | 0966 142 5782 Helpdesk
0917 628 2546 Aftersales

CEBU SRP

Cebu South Coastal Road Barangay San Isidro Talisay City, Cebu 6045
0936 372 3585 Sales | 0966 142 5782 Helpdesk
0917 628 2546 Aftersales

ILOILO

Coastal Road, Barangay Napnud Leganes, Iloilo City, 5003
0936 372 3585 Sales | 0966 142 5782 Helpdesk
0917 628 2546 Aftersales

PALAWAN

Km3, South National Highway, Barangay San Pedro, Puerto Princesa City, Palawan 5300
0936 372 3585 Sales | 0966 142 5782 Helpdesk
0917 628 2546 Aftersales

Mindanao

DAVAO

Door 14-18 Asia Prime Center, G. Del Pilar st., Corner Dacudao Barangay Agdao Proper, Davao City, 8000
0917 125 1306 Sales | 0966 142 5782 Helpdesk
0927 601 4072 Aftersales

DAVAO R.CASTILLO

830 R.Castillo St., Agdao Davao City, 8000
0917 125 1306 Sales | 0966 142 5782 Helpdesk
0927 601 4072 Aftersales

DAVAO DIVERSION

Diversion Road, Buhangin, Davao City, 8000
0917 125 1306 Sales | 0966 142 5782 Helpdesk
0927 601 4072 Aftersales

CAGAYAN DE ORO

Zone 1B, Barangay Taytay, El Salvador City, Misamis Oriental, 9017
0927 601 4079 Sales | 0966 142 5782 Helpdesk
0917 110 5896 Aftersales

SURIGAO

P7, Barangay Gamuton, Carrascal, Surigao del Sur, 8318
0927 601 4079 Sales | 0966 142 5782 Helpdesk
0917 110 5896 Aftersales

GENERAL SANTOS

Door 1 Diversion Road near Crossing mabuhay road Barrio of Nopol, Barangay Conel General Santos City, 9500
0995 314 4524 Sales | 0966 142 5782 Helpdesk
0927 601 4072 Aftersales

BUTUAN

Purok 5 Barangay Lemon 8600 City of Butuan Agusan del Norte, 8600
0927 601 4079 Sales
0966 142 5782 Helpdesk
0917 110 5896 Aftersales

TAGUM - Parts Store

JSP BLDG., Purok Galingan, Barangay Mankilam, Tagum City, Davao del Norte, 8100
0917 103 7042 Sales
0966 142 5782 Helpdesk

ZAMBOANGA - Parts Store

Mayor Jaldon st. Barangay Canelar, Zamboanga City, 7000
0917 139 6974 Sales
0966 142 5782 Helpdesk



Follow us on our Facebook page

CALLING CARD

TRUCKS



HEAVY EQUIPMENT



PARTS



SERVICE CENTER



AFTERSALES SERVICES

Archon Aftersales Services Helpline is ready to assist customer inquiries, complaints, and concerns.